ET-LED-310 LE

Catalog Number:

LED TRACK FIXTURE		Project Name:			
		Note:	Туре:		
LUMEN PACKAGE: UP TO 1100L	NATTAGE: 17W				
		LED MODULE PERFORMANCE Available in 3000K.	HOUSING All tracks are design using a proprietary coolLED Advanced Thermodynamic Design. Heat managemen		
		High color rendering of 90+ CRI and guaranteed color consistency within a 2 step MacAdams Ellipse.	systems are engineered for extremely long life and service period.		
		Guaranteed lumen maintenance of 70% at 50,000 hrs and tested to LM-79 and LM-80 standards by an independent laboratory.	Electronic constant current LED driver compatible wit TRIAC (forward-phase or leading-edge) and input 120' Protections : output open load, over-current and short-cii cuit (hiccup), and over-temperature with auto recovery.		
		Track heads available in a variety of delivered lumen options based on series: 1100L.	Tracks are shipped standard to be compatible with 1 Circuit and 2 Circuit type H track. It is also available for		
		DIMMING INFORMATION Multiple dimming options available, with smooth dim-	2 Circuit 2 Neutral 120V Track.		
		ming down to 10% of full light	Track heads are adjustable up to 360° horizontally an 180° vertically		
		Our LED drivers are rated for 60Hz at 120V input and			
MENSIONS:		produce less than 20% THD, and a power factor between 90% and 100%	Track heads use a friction-based movement system that allows you to adjust and re-adjust track head positionin to deliver light where your need it most. Once the an		
		WARRANTY	gles have been set each track light will stay in place unt		
	1.325"	Five years limited warranty and a minimum 50,000 hours performance at L70.	re-adjusted for the next display.		
			NOTE: Ceiling mount Only.		
		FINISH			
		Track is available in black and white.			



Example: ET-LED-310-1100L-DIMTR-120-FL-30K-90-AWH						
SERIES	LUMENS/DIMMING	OPTICS	STANDARD SERIES CCT/CRI	COLOR		
ET-LED-310	□ 1100L-DIMTR-120	□ FL = 28°	□ 30K-90	 AWH(Architectural White) ABK(Architectural Black) 		

SPECIFICATIONS:

ET-LED-310

LUMEN/DIMMING OPTICS

STANDARD CCT/CRI COLOR

Example: ET-LED-310-1100L-DIMTR-120-FL-30K-90-AWH

elite LED LIGHTING

3.75"

- 1.5" -

Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.





(FL) Flood

20° - 30°

OPTICS

5